



Certificate of Compliance

No. 2P210224.MFPOS69

Certificate's
Holder:

Moulded Fibreglass Products

Corporate Office: 3rd Floor, 65 Cotton Street,
Kolkata – 700 007, West Bengal, India,

Works: Gangarampur Road, Banerjee para,
Maheshtala, Kolkata – 700 141, West Bengal, India.

Certification ECM
Mark:



Product:
Model(s):

Nylon Cable Ties

(see the following annex)

Verification to:

Standard:

EN IEC 62275:2019

related to CE Directive(s):
2014/35/EU (Low Voltage)

Remark: This document has been issued on a voluntary basis and upon request of the manufacturer. It is our opinion that the technical documentation received from the manufacturer is satisfactory for the requirements of the ECM Certification Mark. The conformity mark above can be affixed on the products accordingly to the ECM regulation about its release and its use.

Additional information and clarification about the Marking:



The manufacturer is responsible for the CE Marking process, and if necessary, must refer to a Notified Body. This document has been issued on the basis of the regulation on ECM Voluntary Mark for the certification of products. RG01_ECM rev.3 available at: www.entecerma.it

Issuance date: 24 February 2021

Expiry date: 23 February 2026

Reviewer
Technical expert
Amanda Payne

Approver
ECM Service Director
Luca Bedonni

Ente Certificazione Macchine Srl

Via Ca' Bella, 243 – Loc. Castello di Serravalle – 40053 Valsamoggia (BO) - ITALY
☎ +39 051 6705141 📠 +39 051 6705156 ✉ info@entecerma.it 🌐 www.entecerma.it



Annex I

No. 2P210224.MFPOS69

Product Type	Models
Nylon Cable Ties	A) Miniature Series: Length – 75 to 300 mm Width – 1.8 to 2.7 mm Thickness – 1.0 mm
	B) Intermediate Series: Length – 150 to 350 mm Width – 3.0 to 3.7 mm Thickness – 1.2 mm
	C) Standard Series: Length – 200 to 500 mm Width – 4.0 to 4.8 mm Thickness – 1.3 mm
	D) Heavy Duty Series: Length – 150 to 750 mm Width – 7.6 mm Thickness – 1.6 mm
	E) Extra Heavy Duty Series: Length – 460 to 1230 mm Width – 8.8 mm -12.7mm Thickness – 1.8 mm -2.0mm

RoHS

Certificate of Compliance



No. 2P210224.MFPOS70

Certificate's Holder: Moulded Fibreglass Products
Corporate Office: 3rd Floor, 65 Cotton Street,
 Kolkata – 700 007, West Bengal, India,
Works: Gangarampur Road, Banerjeepara,
 Maheshtala, Kolkata – 700 141, West Bengal, India.

Product: Nylon Cable Ties
Model(s): (see the following annex)

Verification to: **Standard:**
 EN 50581:2012

Related to Directive(s):
 2011/65/EU amended by 2015/863/EU Restriction of
 the use of certain hazardous substances (RoHS)

Remark: This document has been issued on a voluntary basis and upon request of the manufacturer. It is our opinion that the technical documentation received from the manufacturer is satisfactory for the requirements of the ECM Certification Mark. The conformity mark above can be affixed on the products accordingly to the ECM regulation about its release and its use.

Additional information and clarification about the Marking:



The manufacturer is responsible for the CE Marking process, and if necessary, must refer to a Notified Body. This document has been issued on the basis of the regulation on ECM Voluntary Mark for the certification of products. RG01_ECM rev.3 available at: www.entecerma.it

Issuance date: 24 February 2021

Expiry date: 23 February 2026

Reviewer
 Technical expert
 Amanda Payne



Approver
 ECM Service Director
 Luca Bedonni

Ente Certificazione Macchine Srl

Via Ca' Bella, 243 – Loc. Castello di Serravalle – 40053 Valsamoggia (BO) - ITALY
 ☎ +39 051 6705141 📠 +39 051 6705156 ✉ info@entecerma.it 🌐 www.entecerma.it



Annex I

No. 2P210224.MFPOS70

Product Type	Models
Nylon Cable Ties	A) Miniature Series: Length – 75 to 300 mm Width – 1.8 to 2.7 mm Thickness – 1.0 mm
	B) Intermediate Series: Length – 150 to 350 mm Width – 3.0 to 3.7 mm Thickness – 1.2 mm
	C) Standard Series: Length – 200 to 500 mm Width – 4.0 to 4.8 mm Thickness – 1.3 mm
	D) Heavy Duty Series: Length – 150 to 750 mm Width – 7.6 mm Thickness – 1.6 mm
	E) Extra Heavy Duty Series: Length – 460 to 1230 mm Width – 8.8 mm -12.7mm Thickness – 1.8 mm -2.0mm