

CERTIFICATE OF COMPLIANCE

Certificate Number 20130423-E353240
 Report Reference E353240-20130419
 Issue Date 2013-APRIL-23

Issued to: MOULDED FIBREGLASS PRODUCTS
 3RD FL, 65 COTTON STREET
 KOLKATA WB 700007 INDIA

This is to certify that representative samples of

COMPONENT - POSITIONING DEVICES


Standard Nylon Ties - TY 100 x 2.5, TY 150 x 2.5, TY 200 x 2.5, TY 150 x 3.6, TY 200 x 3.6, TY 250 x 3.6, TY 300 x 3.6, TY 200 X 4.8, TY 250 X 4.8, TY 300 X 4.8, TY 364 X 4.8, TY 450 X 4.8, TY 200 X 7.6, TY 300 X 7.6, TY 364 X 7.6, TY 430 X 7.6, TY 530 X 7.6, TY 630 X 8.8, TY 710 X 8.8

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 62275, Cable Management Systems - Cable Ties for Electrical Installations


Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Recognized Component Mark should be considered as being covered by UL's Recognition and Follow-Up Service.

The UL Recognized Component Mark generally consists of the manufacturer's identification and catalog number, model number or other product designation as specified under "Marking" for the particular Recognition as published in the appropriate UL Directory. As a supplementary means of identifying products that have been produced under UL's Component Recognition Program, UL's Recognized Component Mark: , may be used in conjunction with the required Recognized Marks. The Recognized Component Mark is required when specified in the UL Directory preceding the recognitions or under "Markings" for the individual recognitions.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Recognized Component Mark on the product.



William R. Carway, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at gen@ul.com/contact



Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Bundle Diam, mm (in.)		Loop Tensile Strength, N (lbf)	Operating Temp, °C (°F)		Min Installation Temp, °C (°F)	Resistant to UV Light	ANSI/UL 94 Mfl Flame Rating
		Min	Max		Min	Max			
TY 100 x 2.5	11	2 (0.079)	20 (0.787)	80 (18)	-10(14)	85(185)	0(32)	Yes	V-2
TY 150 x 2.5	11	2 (0.079)	35 (1.378)	80 (18)	-10(14)	85(185)	0(32)	Yes	V-2
TY 200 x 2.5	11	3 (0.118)	45 (1.772)	80 (18)	-10(14)	85(185)	0(32)	Yes	V-2
TY 150 x 3.6	11	3 (0.118)	35 (1.378)	130 (29)	-10(14)	85(185)	0(32)	Yes	V-2
TY 200 x 3.6	11	3 (0.118)	49 (1.929)	130 (29)	-10(14)	85(185)	0(32)	Yes	V-2
TY 250 x 3.6	11	3 (0.118)	60(2.362)	130 (29)	-10(14)	85(185)	0(32)	Yes	V-2
TY 300 x 3.6	11	3 (0.118)	75(2.953)	130 (29)	-10(14)	85(185)	0(32)	Yes	V-2
TY 200 X 4.8	11	3 (0.118)	49 (1.929)	220 (50)	-10(14)	85(185)	0(32)	Yes	V-2
TY 250 X 4.8	11	3 (0.118)	60(2.362)	220 (50)	-10(14)	85(185)	0(32)	Yes	V-2
TY 300 X 4.8	11	3 (0.118)	75(2.953)	220 (50)	-10(14)	85(185)	0(32)	Yes	V-2
TY 364 X 4.8	11	3 (0.118)	95(3.740)	220 (50)	-10(14)	85(185)	0(32)	Yes	V-2
TY 450 X 4.8	11	3 (0.118)	115(4.528)	220 (50)	-10(14)	85(185)	0(32)	Yes	V-2
TY 200 X 7.6	11	4 (0.157)	45(1.772)	530 (119)	-10(14)	85(185)	0(32)	Yes	V-2
TY 300 X 7.6	11	4 (0.157)	75(2.953)	530 (119)	-10(14)	85(185)	0(32)	Yes	V-2
TY 364 X 7.6	11	4 (0.157)	98(3.858)	530 (119)	-10(14)	85(185)	0(32)	Yes	V-2
TY 430 X 7.6	11	4 (0.157)	110(4.331)	530 (119)	-10(14)	85(185)	0(32)	Yes	V-2
TY 530 X 7.6	11	10 (0.394)	140(5.512)	530 (119)	-10(14)	85(185)	0(32)	Yes	V-2
TY 630 X 8.8	11	10 (0.394)	175(6.890)	580 (130)	-10(14)	85(185)	0(32)	Yes	V-2
TY 710 X 8.8	11	10 (0.394)	200(7.874)	580 (130)	-10(14)	85(185)	0(32)	Yes	V-2